

G:B:D:



:TOUCHE

**HYDRAULIC
RISING BOLLARDS**





TOUCHE100

Hydraulic rising bollards

The new line of small-size automatic rising bollards (230 Vac hydraulic) with cylinder Ø120 mm, that assures maximum security and practicality.
Suitable for every kind of installation for which a

better esthetical quality is requested, providing a strong anti-breakthrough capacity.
TOUCHE 100 includes the anti-rising safety device in presence of objects or persons on the rising bollard, LED signal lights.

Technical data	TOUCHE120
use	heavy
frequency of use	40%
motor power supply	● 230 Vac - 50/60 Hz
power absorbed	600W
degree of protection	IP67
resistance to impact without deformation	2000 J
resistance to breaking	25000 J
operating pressure	10 bar
opening time	10 s
closing time	15 s
cylinder stroke	700 mm
cylinder thickness	10 mm
operating temperature	-20°C +60°C
operator weight	176 Kg

Accessories





TOUCHE200

Hydraulic rising bollards

The new line of safety automatic rising bollards (230Vac hydraulic) with diameter 275 mm and thickness 10 mm, that provide the strongest anti-breakthrough capacity. Its high rising speed also allows installation in

areas with heavy traffic. TOUCHE 200 includes the anti-rising safety device in presence of objects or persons on the rising bollard, LED signal lights.

Technical data	TOUCHE275
use	heavy
frequency of use	40%
motor power supply	● 230 Vac - 50/60 Hz
power absorbed	600W
degree of protection	IP67
resistance to impact without deformation	15000 J
resistance to breaking	350000 J
operating pressure	10 bar
opening time	7 s (10 s with single control unit)
closing time	10 s (15 s with single control unit)
cylinder stroke	700 mm
cylinder thickness	10 mm
operating temperature	-20°C +60°C
operator weight	340 Kg

Accessories



• AUTOMAZIONE ACCESSI

 a **BANDINI INDUSTRIE** company



Associated



GIBIDI

GI.BI.DI. S.r.l.

Via Abetone Brennero, 177/B
46025 Poggio Rusco (MN) - ITALY
Tel. +39.0386.52.20.11
Fax +39.0386.52.20.31
info@gibidi.com

www.gibidi.com