




Composition KIT BH30/806

Code	Description	QTY
BH30/804	Electromechanical BRUSHLESS motor, low voltage, super intensive use, with native encoder onboard, irreversible ideal for sliding gates up to 800-1000 kg with built-in digital controller B70 series, magnetic limit switch.	1
H93/RX22A/I	Plug-in receiver 2 channels 433,92 Mhz for control unit series H70, B70, EDGE and AG/CTRL.	1
E80/TX52R/2	Fix code transmitter 433,92 Mhz. 2 channels, with radio for copy.	2
R90/F4ES	Pair of external photocells synchronized 24V AC/DC (max. 4 pairs).	1
FIFTHY/24	LED flashing light series FIFTHY 24V with integrated antenna.	1
R99/C/001	Signboard "Automatic Opening"	1


Product technical specifications	KIT BH30/806
Max gate weight	800-1000 kg
Power line supply	230V AC - 50Hz
Motor power supply	24V
Power rating	200W
Frequency of use	Intensive use
Thrust	50 - 1000N
Operating temperature	-20+55°C
Protection level	IP43
Reductor Type	Irreversible
Manoeuvre speed	12 m/min (0.20 m/s)
Limit switch	Magnetic
Onboard control unit	B70/1DC
Encoder	Digital native encoder + magnetic digital SENSORED, 4096 PPR
Batteries recovery	Optional 2 internal battery 12V 1,2AH - Optional 2 external battery 12V 4,5AH
Type exit gear	Z15/mod 4
Operating cycles per day (opening/closing - 24 hours no stop)	1300
Maximum dimension product in mm (L x W x H)	315 x 165,8 x 329
Product weight packed (Kg)	12,7

PRODUCT DIMENSIONS




DIMENSIONS

PRODUCT PREPARING FOR INSTALLATION



PREDISPOSITION FOR STANDARD INSTALLATION



PREDISPOSITION FOR STANDARD INSTALLATION

PRODUCT ACCESSORIES



B71/BC
Batteries charger for
brushless digital
controller B70/1DC.



BT12V12
Pair of batteries 12V 1.2
Ah.



BT12V45
Pair of batteries 12V 4.5
Ah.



KT214
Fixing plate with stay
bolts and screws H30
series.



KT214/SC
Adapter plate with stay
bolts and screws H30
series.



KT221
Raised fixing plate for
H30 series (+3,5 cm).



HT418
External box without
batteries, for battery
BT12V45 (12V DC 4,5 Ah)



GA550
Galvanised steel rack
22x22x1000 module 4.



GA551
Galvanised steel rack
30x12x1000 module 4
with spacers and screws.



GA553
Nylon rack module 4 with
6 connectors L.1000.



GA554
Pocket of 6 spacers (2,5
Cm) and screws.



MC775
Kit magnetic limit switch
for control unit
H70/103AC, H70/104AC,
B70/1DC, B70/1DCHP.



R99/C/001
Signboard Automatic
Opening".