



Composition KIT H70/22

Code	Description	QTY
H70/200AC/BOX	Control unit for 2 motors 230V AC with slow down, with plastic box.	1
H93/RX22A/I	Plug-in receiver 2 channels 433,92 Mhz for control unit series H70, B70, EDGE and AG/CTRL.	1
E80/TX52R/2	Fix code transmitter 433,92 Mhz. 2 channels, with radio for copy.	2
R90/F2ES	Pair of external photocells synchronized.	1
R92/LED230	LED flashing light series R92 230V AC.	1
R91/AN1/LR1	Antenna for flashing light R92 series	1
R99/C/001	Signboard "Automatic Opening"	1

Product technical specifications	KIT H70/22
Power line supply	230V AC - 50Hz
Operating temperature	-10+55 C°
Protection level	IP54
N. motors activated	2 asynchronous monophase
Max power per motor	600W 230Vac
Max courtesy light charge	100W (12-230V ac/dc)
Max power gate open light	2W 24Vac
Max voltage accessories output	350mA 24Vac (500mA 24Vcc)
Max flashing light charge	40W (12-230V ac/dc)
Maximum dimension product in mm (L x W x H)	228 x 307 x 118
Product weight packed (Kg)	2.8
Number items per pallet	49



H70/EL
Electric lock module
12V for control unit
H70/200AC -
H70/104AC -
H70/105AC.