







Code	Description	Pcs/pallet
R21/351	Electromechanical underground motor 230V AC irreversible ideal for swing gates with leaf up to 3,5 mt. Standard version with 2 mt cable.	50

Product technical specifications	R21/351
Power line supply	230V AC - 50Hz
Motor power supply	230V AC
Power rating	200W
Frequency of use	30%
Torque	300 N m
Operating temperature	-20+55°C
Protection level	IP67
Reductor Type	Irreversible
Manoeuvre speed	1,2 Rpm
Opening time at 90°	19 s
Motor thermal protection	150°C
Limit switch	Mechanical stoppers
Encoder	Optional as an accessory
Maximun opening	105° (optional 125° - 360°)
Power supply cable length	2m
Bearing on main shaft	Standard
Maximum dimension product in mm (L x W x H)	345 x 224 x 144
Product weight packed (Kg)	14,1
Number items per pallet	50

PRODUCT DIMENSIONS



DIMENSIONS



DIMENSIONS

PRODUCT ACCESSORIES



FU100
Cold galvanised
foundation box and lid.



FU101
Hot galvanised
foundation box and lid.



FU102
Hot galvanised
foundation box and inox
lid.



FU103
Inox AISI 304 foundation
box and lid.



LT300
Levers for opening up to
125°.



LT301
Levers for opening up to
360°.



LT301/R
Levers for opening up to
360°, with reinforced
chain.



LT300/90SX
Levers for opening up to
125° - 90° turned - left.



LT300/90DX
Levers for opening up to
125° - 90° turned - right.



LT327/SC
Pinion gear ¼ Z13 of
adaptation in pinion
ombining ¼ Z16.



R21/ENC/2
Module encoder for R21
series with 2 mt cable.



RL650
Release system with
standard lever.



RL650/R
Release system with
standard lever, reinforced
steel version.



RL651
Release system with
european cylinder key.



RL663
Long release lever for
underground.



R99/C/001
Signboard Automatic
Opening".