

G:B:D:



:TOP

**OPERATORS
FOR SWING GATES**



TOP

Linear hydraulic operators for swing gates

The TOP series range is suitable for any type of installation and for both residential and heavy use for leafs up to 6 m. The streamlined design and absolutely silent operation make the operator suitable for any type of gate.

The vacuum hydraulic circuit prevents air heat exchange and hence possible formation of condensate, thus guaranteeing hydraulic efficiency of the piston over time.

The opening and closing force can be regulated by means of the overpressure valves for the highest level of safety against crushing as required by the

EN 12453 standards.

The models are available in three versions: Always Released (SLAC): in manual manoeuvres the leaf is not slowed down by the presence of the piston. Always Locked (BAC): the piston assures excellent hold and can be released simply by acting on the unlocking device, also available with European Profile personalised key (optional).

Always released during opening and always locked during closing (SLA-BA): ideal for large leafs where locking when opened is required (wind resistance).

Technical data	TOP291	TOP391	TOP441	TOP291/S	TOP391/S	TOP441/S
use	residential	heavy	heavy	residential	heavy	heavy
frequency of use	30%	50%	50%	30%	55%	55%
motor power supply	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz	● 230 Vac - 50/60 Hz
power absorbed	170W	190W	190W	170W	190W	190W
degree of protection	IP65	IP65	IP65	IP65	IP65	IP65
rod speed	10 mm/s	10 mm/s	10 mm/s	20 mm/s	20 mm/s	20 mm/s
maximum rod stroke	290 mm	290 mm	440 mm	290 mm	290 mm	440 mm
maximum thrust force	3000 N	4500 N	4500 N	2200 N	3000 N	3000 N
nominal force	2500 N	3000 N	3000 N	1500 N	2200 N	2200 N
force regulation	hydraulic	hydraulic	hydraulic	hydraulic	hydraulic	hydraulic
speed regulation	YES **	YES **	YES **	YES **	YES **	YES **
maximum leaf length	3.5 m *	4.5 m *	6.0 m *	3.5 m *	4.5 m *	6.0 m *
operating temperature	-20°C +60°C	-20°C +60°C	-20°C +60°C	-20°C +60°C	-20°C +60°C	-20°C +60°C
thermal switch	100°C	100°C	100°C	100°C	100°C	100°C
operator weight	7.7 Kg	8.7 Kg	10 Kg	7.7 Kg	8.7 Kg	10 Kg

* in case of application on panelled / hollow-core leaves or longer than 2,5 m, we suggest the use of an electric lock

** by proper control unit: BA230

Accessories



 a **BANDINI INDUSTRIE** company



Associated



GIBIDI

GI.BI.DI. S.r.l.

Via Abetone Brennero, 177/B
46025 Poggio Rusco (MN) - ITALY
Tel. +39.0386.52.20.11
Fax +39.0386.52.20.31
info@gibidi.com

www.gibidi.com